

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations Revision Date: 09/28/2016 Date of Issue: 09/28/2016

Version: 1.0

# **SECTION 1: IDENTIFICATION**

1.1. Product Identifier Product Form: Mixture

Product Name: PTFE Coated Fiberglass Thread

Synonyms: Coated fiberglass thread

1.2. Intended Use of the Product
Use of the Substance/Mixture: Sewing.

1.3. Name, Address, and Telephone of the Responsible Party

Company

NEWTEX INDUSTRIES, INC. 8050 Victor-Mendon Road Victor, New York 14564 (585) 924-9135

1.4. Emergency Telephone Number

**Emergency Number** : 1-800-836-1001

## **SECTION 2: HAZARDS IDENTIFICATION**

## 2.1. Classification of the Substance or Mixture

#### **GHS-US Classification**

Not classified

## 2.2. Label Elements

#### **GHS-US Labeling**

No labeling applicable

#### 2.3. Other Hazards

The following applies to the product if it is cut, sanded or altered in such a way that excessive and/or significant particulates and/or dusts may be generated: Exposure may aggravate pre-existing eye, skin, or respiratory conditions. Dust may cause mechanical irritation to eyes, nose, throat, and lungs. If small particles are generated during further processing, handling or by other means, may form combustible dust concentrations in air. Inhalation of fumes from overheating "TEFLON" PTFE may cause polymer fume fever, a temporary flu-like illness with fever, chills and sometimes cough, of approximately 24 hours duration.

#### 2.4. Unknown Acute Toxicity (GHS-US)

No data available

# **SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**

# 3.1. Substance

Not applicable

# 3.2. Mixture

Name	Product Identifier	%	GHS-US classification
Glass, oxide, chemicals	(CAS No) 65997-17-3	80 - 90	Carc. 2, H351*
Polytetrafluoroethylene	(CAS No) 9002-84-0	10 - 20	Comb. Dust
Silicone Thread Lubricant	(CAS No) Proprietary	<= 5	Not classified
Various High Temperature Pigment	(CAS No) Proprietary	<= 2	Not classified

<sup>\*</sup>Fiberglass is typically classified as a Carc. 2, H351. However, the fiberglass found in this product are non-respirable, continuous filament fibers. There are no known health effects from the long term use or contact with these fibers. For more information, see Section 11.

The specific chemical identity and/or exact percentage of composition have been withheld as a trade secret [29 CFR 1910.1200] Full text of H-phrases: see section 16

# **SECTION 4: FIRST AID MEASURES**

## 4.1. Description of First-aid Measures

**First-aid Measures General:** Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

**First-aid Measures After Inhalation:** When symptoms occur: go into open air and ventilate suspected area. Obtain medical attention if breathing difficulty persists.

**First-aid Measures After Skin Contact:** Gently wash with plenty of soap and water. Obtain medical attention if irritation develops or persists.

09/28/2016 EN (English US) 1/5

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

**First-aid Measures After Eye Contact:** No health effects expected. If irritation does occur, flush with lukewarm, gently flowing water for 5 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention if irritation develops or persists.

First-aid Measures After Ingestion: Rinse mouth. Do NOT induce vomiting. Obtain medical attention.

# 4.2. Most Important Symptoms and Effects Both Acute and Delayed

Symptoms/Injuries: Not expected to present a significant hazard under anticipated conditions of normal use.

**Symptoms/Injuries After Inhalation:** For particulates, dust, or fumes from processing: Prolonged contact with large amounts of dust may cause mechanical irritation. Inhalation of fumes from overheating "TEFLON" PTFE may cause polymer fume fever, a temporary flu-like illness with fever, chills and sometimes cough, of approximately 24 hours duration.

Symptoms/Injuries After Skin Contact: Prolonged exposure may cause skin irritation.

Symptoms/Injuries After Eye Contact: May cause slight irritation to eyes.

**Symptoms/Injuries After Ingestion:** Not expected to be a primary route of exposure. May cause irritation of the gastrointestinal tract.

**Chronic Symptoms:** Repeated or prolonged contact with skin may cause dermatitis. There are no known health effects from the long term use or contact with non-respirable continuous filament fibers, which is the type of fiberglass that is used. Non-respirable fibers cannot reach the deep lung because they have a diameter of greater than 3.5 micrometers. Fibers of this diameter cannot penetrate the narrow, bending passages of the human respiratory tract to reach the lower regions of the lung, and thus have no possibility of causing serious pulmonary damage. They deposit on the surfaces of the upper respiratory tract, nose, or pharynx. These fibers are then cleared through normal physiological mechanisms.

# 4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention. If medical advice is needed, have product container or label at hand.

# **SECTION 5: FIRE-FIGHTING MEASURES**

#### 5.1. Extinguishing Media

Suitable Extinguishing Media: Use extinguishing media appropriate for surrounding fire.

Unsuitable Extinguishing Media: Do not use a heavy water stream. Use of heavy stream of water may spread fire.

# 5.2. Special Hazards Arising From the Substance or Mixture

**Fire Hazard:** Not considered flammable but may burn at high temperatures.

**Explosion Hazard:** Product is not explosive. If excessive dust is generated from processing, it may present a dust explosion hazard when dispersed in air at sufficient quantities in the presence of an ignition source.

Reactivity: Hazardous reactions will not occur under normal conditions.

# 5.3. Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire.

Firefighting Instructions: Use water spray or fog for cooling exposed containers.

**Protection During Firefighting:** Do not enter fire area without proper protective equipment, including respiratory protection.

**Hazardous Combustion Products:** Highly toxic and corrosive gases are released.

# **SECTION 6: ACCIDENTAL RELEASE MEASURES**

# 6.1. Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Avoid prolonged contact with eyes, skin and clothing. Avoid breathing dust.

# 6.1.1. For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protection equipment (PPE).

**Emergency Procedures:** Evacuate unnecessary personnel.

#### 6.1.2. For Emergency Personnel

**Protective Equipment:** Equip cleanup crew with proper protection.

**Emergency Procedures:** Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit. Ventilate area.

# 6.2. Environmental Precautions

Prevent entry to sewers and public waters.

## 6.3. Methods and Materials for Containment and Cleaning Up

For Containment: Contain solid spills with appropriate barriers and prevent migration and entry into sewers or streams.

**Methods for Cleaning Up:** Clean up spills immediately and dispose of waste safely. Recover the product by vacuuming, shoveling or sweeping. Avoid generation of dust during clean-up of spills. Transfer spilled material to a suitable container for disposal. Contact competent authorities after a spill.

## 6.4. Reference to Other Sections

See Section 8 for exposure controls and personal protection and Section 13 for disposal considerations.

09/28/2016 EN (English US) 2/5

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

# **SECTION 7: HANDLING AND STORAGE**

# **Precautions for Safe Handling**

Additional Hazards When Processed: If processed in such a way that dust may be generated, may present a dust explosion hazard in air.

Precautions for Safe Handling: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Avoid prolonged contact with eyes, skin and clothing. The following applies to the product if it is cut, sanded or altered in such a way that excessive and/or significant particulates and/or dusts may be generated: Avoid breathing dust. Avoid dust formation.

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures.

## **Conditions for Safe Storage, Including Any Incompatibilities**

**Technical Measures:** Comply with applicable regulations.

Storage Conditions: Keep container closed when not in use. Store in a dry, cool place. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials.

Incompatible Products: Strong acids, strong bases, strong oxidizers.

#### Specific End Use(s) 7.3.

Sewing.

# SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

#### **Control Parameters**

For substances listed in section 3 that are not listed here, there are no established exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), AIHA (WEEL), NIOSH (REL), or OSHA (PEL).

11 / 1	<u> </u>	, , ,	
Glass, oxide,	chemicals (65997-17-3)		
USA NIOSH	NIOSH REL (TWA) (mg/m³)		3 fibers/cm³ (fibers ≤3.5 μm in diameter & ≥10μm in length), TWA 5mg/m3 (total)
USA OSHA	OSHA PEL (TWA) (mg/m³)		15 mg/m³ total dust, 5 mg/m3, respirable fraction 8 hr

#### 8.2. **Exposure Controls**

**Appropriate Engineering Controls** 

: Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure adequate ventilation, especially in confined areas. Ensure all national/local regulations are observed.

**Personal Protective Equipment** 

: Gloves. Protective clothing. Safety glasses with side-shields.







**Materials for Protective Clothing** 

**Hand Protection Eve Protection** 

Skin and Body Protection **Respiratory Protection** 

: Wear suitable protective clothing.

: Wear protective gloves.

: Safety glasses with side-shields. : Wear suitable protective clothing.

: If exposure limits are exceeded or irritation is experienced, approved respiratory protection should be worn. In case of inadequate ventilation, oxygen deficient atmosphere, or where exposure levels are not known wear approved respiratory

protection.

**Other Information** When using, do not eat, drink or smoke.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

#### 9.1. **Information on Basic Physical and Chemical Properties**

**Physical State** 

**Appearance** : White filament fiberglass coated with brown PTFE coating

Odor No significant odor **Odor Threshold** : No data available

рΗ : Not applicable **Evaporation Rate** : Not applicable **Melting Point** : No data available **Freezing Point** : Not applicable **Boiling Point** : Not applicable

**Flash Point** : 348.89 °C (660 °F) (lubricant)

09/28/2016 3/5 EN (English US)

Safety Data Sheet

Viscosity

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

**Auto-ignition Temperature** : No data available **Decomposition Temperature** : 300 °C (572 °F) Flammability (solid, gas) : No data available **Vapor Pressure** : Not applicable Relative Vapor Density at 20°C Not applicable **Relative Density** : No data available : Insoluble Solubility **Partition Coefficient: N-Octanol/Water** : Not applicable

**9.2.** Other Information No additional information available

# **SECTION 10: STABILITY AND REACTIVITY**

- 10.1. Reactivity: Hazardous reactions will not occur under normal conditions.
- 10.2. Chemical Stability: Stable under recommended handling and storage conditions (see section 7).
- 10.3. Possibility of Hazardous Reactions: Hazardous polymerization will not occur.
- **10.4. Conditions to Avoid:** Direct sunlight, extremely high or low temperatures, and incompatible materials.
- **10.5. Incompatible Materials:** Strong acids, strong bases, strong oxidizers.
- **10.6.** Hazardous Decomposition Products: Thermal decomposition generates: Toxic gases. Corrosive vapors.

# **SECTION 11: TOXICOLOGICAL INFORMATION**

# 11.1. Information on Toxicological Effects

Acute Toxicity: Not classified

Skin Corrosion/Irritation: Not classified
Serious Eye Damage/Irritation: Not classified
Respiratory or Skin Sensitization: Not classified

Germ Cell Mutagenicity: Not classified

**Carcinogenicity:** Not classified. (There are no known health effects from the long term use or contact with non-respirable continuous filament fibers, which is the type of fiberglass that is used. Non-respirable fibers cannot reach the deep lung because they have a diameter of greater than 3.5 micrometers. Fibers of this diameter cannot penetrate the narrow, bending passages of the human respiratory tract to reach the lower regions of the lung, and thus have no possibility of causing serious pulmonary damage. They deposit on the surfaces of the upper respiratory tract, nose, or pharynx. These fibers are then cleared through normal physiological mechanisms)

: Not applicable

Polytetrafluoroethylene (9002-84-0)	
IARC group	3
Glass, oxide, chemicals (65997-17-3)	
IARC group	2B

Reproductive Toxicity: Not classified

Specific Target Organ Toxicity (Single Exposure): Not classified Specific Target Organ Toxicity (Repeated Exposure): Not classified

Aspiration Hazard: Not classified

**Symptoms/Injuries After Inhalation:** For particulates, dust, or fumes from processing: Prolonged contact with large amounts of dust may cause mechanical irritation. Inhalation of fumes from overheating "TEFLON" PTFE may cause polymer fume fever, a temporary flu-like illness with fever, chills and sometimes cough, of approximately 24 hours duration.

Symptoms/Injuries After Skin Contact: Prolonged exposure may cause skin irritation.

Symptoms/Injuries After Eye Contact: May cause slight irritation to eyes.

**Symptoms/Injuries After Ingestion:** Not expected to be a primary route of exposure. May cause irritation of the gastrointestinal tract.

**Chronic Symptoms:** Repeated or prolonged contact with skin may cause dermatitis. There are no known health effects from the long term use or contact with non-respirable continuous filament fibers, which is the type of fiberglass that is used. Non-respirable fibers cannot reach the deep lung because they have a diameter of greater than 3.5 micrometers. Fibers of this diameter cannot penetrate the narrow, bending passages of the human respiratory tract to reach the lower regions of the lung, and thus have no possibility of causing serious pulmonary damage. They deposit on the surfaces of the upper respiratory tract, nose, or pharynx. These fibers are then cleared through normal physiological mechanisms.

09/28/2016 EN (English US) 4/5

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

# **SECTION 12: ECOLOGICAL INFORMATION**

12.1. Toxicity

**Ecology - General** : Not classified.

#### 12.2. Persistence and Degradability

PTFE Coated Fiberglass Thread	
Persistence and Degradability	Not established.

# 12.3. Bioaccumulative Potential

PTFE Coated Fiberglass Thread	
Bioaccumulative Potential	Not established.

- **12.4. Mobility in Soil** No additional information available
- 12.5. Other Adverse Effects

**Other Information** : Avoid release to the environment.

# **SECTION 13: DISPOSAL CONSIDERATIONS**

#### 13.1. Waste Treatment Methods

**Waste Disposal Recommendations:** Dispose of contents/container in accordance with local, regional, national, and international regulations.

Ecology - Waste Materials: Avoid release to the environment.

# **SECTION 14: TRANSPORT INFORMATION**

The shipping description(s) stated herein were prepared in accordance with certain assumptions at the time the SDS was authored, and can vary based on a number of variables that may or may not have been known at the time the SDS was issued.

- **14.1.** In Accordance with DOT Not regulated for transport
- 14.2. In Accordance with IMDG Not regulated for transport
- 14.3. In Accordance with IATA Not regulated for transport

# **SECTION 15: REGULATORY INFORMATION**

## 15.1. US Federal Regulations

Polytetrafluoroethylene (9002-84-0)	
Listed on the United States TSCA (Toxic Sub	ostances Control Act) inventory
EPA TSCA Regulatory Flag	XU - XU - indicates a substance exempt from reporting under the Inventory Update Reporting Rule, i.e, Partial Updating of the TSCA Inventory Data Base Production and Site Reports (40 CFR 710(C))
Glass, oxide, chemicals (65997-17-3)	
Listed on the United States TSCA (Toxic Sub	ostances Control Act) inventory

## 15.2. US State Regulations

Polytetrafluoroethylene (9002-84-0)	
U.S Pennsylvania - RTK (Right to Know) List	

# SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

**Revision Date** : 09/28/2016

 Other Information
 : This document has been prepared in accordance with the SDS

requirements of the OSHA Hazard Communication Standard 29 CFR

1910.1200

# **GHS Full Text Phrases:**

Carc. 2	Carcinogenicity Category 2
Comb. Dust	Combustible Dust
H351	Suspected of causing cancer

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

SDS US (GHS HazCom)

09/28/2016 EN (English US) 5/5